



VersaStreamer SDI

1080p60 HEVC Encoder

- Simultaneous streaming to 3 online platforms
- Local recording while streaming
- SDI input for professional workflows



Technical Specifications

Video Encoding

Input Resolutions

1080i/p60, i/p59.94, i/p50, p30, p29.97, p25, p24, p23.98

720p60, p59.94, p50

576i/p50

480i/p60, i/p59.94

Encode Resolutions

1080p60, p59.94, p50, p30, p29.97, p25, p24, p23.98

720p60, p59.94, p50

576p50

540p*

480p60, p59.94

360p*; 270p*; 180p*

(*scaled resolutions, frame rate same as source)

Compression: H.265/HEVC, H.264, Baseline, Main, High

Bit rates: 500kbps - 30Mbps

Rate control: Variable, Constant

Audio Encoding

Encode Format: MPEG-4 AAC-LC in ADTS

64/96/128/192/256/320/384/512 kbps

Encode Sampling Freq: 32, 44.1, 48KHz

General

+12V Input; 8 Watts total

IEEE802.3af Power over Ethernet

Dimensions: 1.5" x 5.0" x 4.234"

Action Button to start/stop RTMP streaming

I/O

Video

HDMI v1.4a input

3G-SDI input

SMTPE-344-2 608/708 Closed Captions (HD)

Audio

3.5mm Analog Audio input - *Line level*

Embedded HDMI input

Embedded SDI input

Recording

USB 3.0

SD Card

Network

10/100/1000 Ethernet (RJ-45)

Simultaneous Streaming and Recording Capabilities

Streaming

RTMP/RTMPS x 3

RTSP

Unicast x 2 (RTP over UDP, Raw UDP)

Multicast (RTP over UDP, Raw UDP)

HLS

Recording

USB/SD Card (MPEG-TS or MP4)

FTP upload

Network and Control

REST API integrates with third-party controllers

Web browser Interface

DHCP (Default) / Static IP Address

XML Polling